



TiTANIUM
SYSTEMS LLC

Flexible Joint Sealant

Concrete Repair Products
Engineered to Last



ADVANTAGES

- **SIMPLE**
Easy to install, Do-it-yourself,
Quick and easy surface preparation
- **DURABLE**
Able to withstand heavy duty traffic
- **CONVENIENT**
Pre-measured tubes
- **ECONOMICAL**
Low cost, Few special tools needed
- **FAST**
Back in service in as little as 1 hour

BENEFITS

- Reduces maintenance costs and damage to lift truck wheels
- Helps prevent joints from further eroding and cracking
- Eliminates tripping and other safety hazards
- 100% solids – No solvent odor
- **Won't allow dirt, pallet chips, and other debris to collect in the joint!**

Visit
www.titanium-systems.com
for more info





Flexible Joint Sealant Application Instructions

CARTRIDGE ASSEMBLY

- 1 Hold tubes with the tip facing upward, remove closed end from tube set with a screwdriver.
- 2 Place static mixing nozzle over the tubes and slip screw collar over the tip and tighten.
- 3 Place tube set into dual cartridge caulking gun.

***Do not allow material to mix prior to use.
The material will cure within 1 to 2 minutes.***



STEP 1 Prepare Area

Remove all loose concrete, previous joint compound or other foreign material to leave a clean sound joint at least 1/2" deep. Vacuum all dirt, dust, and foreign contaminants to assure a trouble free bond.



STEP 2

Place a backer rod into joint. The joint depth should be at least half the joint width from the top of the backer rod to the top of the joint with a minimum 1/2".



STEP 3

Dispense small beginning portion onto cardboard to discard any unmixed material. Apply mixed material by pumping in a continuous motion into the expansion joint.



Scan to
Learn More



Call for a
free facility survey

847.533.9625

www.titanium-systems.com



TiTANIUM
SYSTEMS LLC

INSPIRED ■ INDUSTRIAL ■ SOLUTIONS