



TiTANIUM
SYSTEMS LLC

Epoxy Mortar Patch Kits

Concrete Repair Products
Engineered to Last

ADVANTAGES

- **SIMPLE**
Easy to install, Do-it-yourself,
- **DURABLE**
Permanent patching of concrete
- **CONVENIENT**
Pre-measured packaging
- **ECONOMICAL**
Low cost, Few special tools needed
- **FAST**
Forklift traffic in as little as 6 hours

BENEFITS

- Reduces maintenance costs
- Reduces damaged inventory
- Eliminates tripping and other safety hazards
- 100% solids – No solvent odor



Before



After



■ Everything you need to patch the floor is in the bucket.

Buried in the sand are two metal cans containing parts A and B of the epoxy. These will be mixed with the sand to create your mortar mix.

Visit

www.titanium-systems.com
for more info



Epoxy Mortar Patch Kits Installation Instructions



Prepare damaged area

1 Clean out the area to be patched with a wire brush, wire wheel attachment on the drill, or a concrete grinder. Remove any loose pieces of concrete and stone.

2 Vacuum the area to be patched to remove dirt, dust, and loose concrete.



Mix liquid parts A & B, then slowly add sand

3 Prior to mixing the material, prepare enough holes and cracks to use the entire mix of epoxy mortar. Once the material is mixed, you have approximately 30 to 40 minutes of working time.

4 In a separate container, mix liquid parts A and B with the mixer attachment on the drill. Use the entire container of each.



Apply mix to damaged area and smooth with trowel

5 Slowly add the sand to the mixed liquid and mix with the drill mixer attachment until fully blended.

6 Using the trowel, fill the prepared areas and finish smoothly with the trowel.

Available in two
convenient sizes

Scan to
Learn More



Covers **43 sq ft**
at 1/8" depth



Covers **11 sq ft**
at 1/8" depth

847.533.9625

www.titanium-systems.com



TiTANIUM
SYSTEMS LLC

INSPIRED ■ INDUSTRIAL ■ SOLUTIONS